

Mounting: wall
Environment: indoor (dry location)
Description: Chrome-plated metal frame. White or red satin blown glass diffuser.
Colours: V006BI ○ V006R ●


Certifications: 

Emergency: Without
Dimming: dimmable only with remote light dimmer and dimmable lighting source
Voltage (V): 120 V


CODE	SIZE	LIGHT SOURCE
ULM006/1+V006..	4.3" × 6.7" × 6.7"	⦿ 1x60W (IN) G16 ¹ / ₂ Candelabra E12 2" 2 ⁷ / ₈ "
ULM006/12+V006..	12.6" × 6.7" × 6.7"	⦿ 2x60W (IN) G16 ¹ / ₂ Candelabra E12 2" 2 ⁷ / ₈ "

CODE	DESCRIPTION	PACKAGING SIZE	NET WEIGHT	GROSS WEIGHT
ULM006/1	mounting	7.8" × 6.2" × 4.3"	lbs 0.7	lbs 1.1
ULM006/2	mounting	12.1" × 14.4" × 6.6"	lbs 1.5	lbs 2.6
V006..	diffuser	6.6" × 6.2" × 6.2"	lbs 0,4	lbs 1.1

PHOTOMETRIC CURVES



UM006/1



UM006/2

