

OORT

Jacopo Roda, 2022

The OORT system is composed of tubular elements made of borosilicate glass. Inside them are flexible LED light tubes of the latest generation, easily replaceable, with perfectly uniform 360° light emission and certified also for outdoor use. The borosilicate glass is ribbed on the inside, a feature that enhances the light by making it warm and welcoming, brings out the effect of light and shadow, and allows easy cleaning of the smooth outer surface. The light is diffuse, dimmable and available at 3000K (1900Lm/m) or Dim To Warm which allows to change the colour temperature, by dimming, from minumum 1800K to 4000K at maximum intensity. The flux is dimmer-dependent to a maximum of approx 1000Lm/m. The product can be supplied at 2700K on request.

The floor-to-ceiling lamp with diffused and dimmable light emission. A counterweight on the floor and a ceiling hook in black nickel. Black power cable, dimmer and plug. Plug-in power supply with interchangeable plugs (UK, USA, Europe, Australia). Integrated led. The lamp keeps memory of the last dimming setting. The product with integrated Casambi control system available on request.

MADE IN

ΙT

Nickel black

ALIMENTATION CABLE

Black

GROUP TENSION

Led included - DTW

DIMMER

Dimmer included

ENERGY CLASS

G

CERTIFICATIONS CEIP20

LIGHT SOURCE

LED 18W (DTW da 1800K a 4000K)

COLOR DESCRIPTION SKU

SKU

OORT00010