

## **OORT**

Jacopo Roda, 2022

The OORT system is composed of tubular elements made of borosilicate glass. Inside them are flexible LED light tubes of the latest generation, easily replaceable, with perfectly uniform 360° light emission and certified also for outdoor use. The borosilicate glass is ribbed on the inside, a feature that enhances the light by making it warm and welcoming, brings out the effect of light and shadow, and allows easy cleaning of the smooth outer surface. The light is diffuse, dimmable and available at 3000K (1900Lm/m) or Dim To Warm which allows to change the colour temperature, by dimming, from minumum 1800K to 4000K at maximum intensity. The flux is dimmer-dependent to a maximum of approx 1000Lm/m. The product can be supplied at 2700K on request.

The suspension version is available in horizontal and vertical models, both also in multiple compositions and different heights. Off-centre ceiling rose for electrical connection in white finish. Dimmable ballast. Integrated LED.

MADE IN

ΙT

**ALIMENTATION CABLE** 

Black

**DIMMER** 

Yes, 1-10V/PUSH

CERTIFICATIONS CEIP20

**COLOR DESCRIPTION SKU** 

Nickel black

**GROUP TENSION** 

Led included - DTW

**ENERGY CLASS** 

G

LIGHT SOURCE

LED 18W (DTW da 1800K a 4000K)

SKU

OORT00012